



KIT VUOTO E CARICA



Bomboletta non inclusa



Particolare del kit dotato di elettrovalvola e vacuometro

KIT K-EX-46D/D6

Kit vuoto e carica per R600a-R290-R1270

In conformità con le raccomandazioni sulla sicurezza sul lavoro nell'utilizzo di idrocarburi e refrigeranti infiammabili, il kit è dotato di pompa per vuoto certificata ATEX nelle due versioni senza **A** e con elettrovalvola-vacuometro **B**.

Il kit è dotato del kit di assemblaggio rapido del gruppo manometrico sulla pompa per vuoto brevettato da WIGAM.

Tutti i componenti sono forniti in comodo baule per la semplice movimentazione.

Equipaggiato con:

- Pompa per vuoto RS3D-EX Atex (Zona 2).
- Gruppo manometrico 4 vie a pistone, manometri Ø 80, bagno d'olio per R600a-R290-R1270.
- 2 tubi flessibili 1500 mm, 1/4"SAE.
- 2 valvole accesso LOCK-VALVE 1/4" - SAE F x 1/4" SAE M.
- 1 tubo scarico vapore 5 mt.
- Bilancia elettronica da 5kg, risoluzione 1g.
- 2 supporti bombola (R290 e R600a).
- 1 flacone olio minerale.

Rif	Codice	Modello
A	01010008001	K-EX46D/D6
B	01010008003	K-EX-EV-46D/D6

Rif	Codice	Dimensioni	Peso
A	01010008001	550 x 330 x 360 mm	12,8 kg
B	01010008003	550 x 330 x 360 mm	12,8 kg




Caratteristiche tecniche

Portata bilancia	5 kg
Portata pompa	46 lt/min
Vuoto finale	1x10 ⁻² mbar



Ricambi



Rif	Codice	Modello	Descrizione	Q.tà Min.
A	06053010		Tubo scarico vapore 5 mt	-
B	06071002001	GYSS/4-4/60 B	Tubo flessibile 1500 mm 1/4 x 1/4 - Blu	-
C	06071002002	GYSS/4-4/60 R	Tubo flessibile 1500 mm 1/4 x 1/4 - Rosso	-
D	12002003	K1L	Olio minerale 1lt	12 pz



VACUUM AND CHARGING KIT



Cartridge not included



Detail of the kit with solenoid valve and vacuum meter

KIT K-EX-46D/D6

Vacuum and charging kit for R600a-R290-R1270

In compliance with the work safety recommendations when using hydrocarbons and flammable refrigerants, the kit is equipped with an ATEX-certified vacuum pump in the two versions with **A** and with solenoid valve and vacuum meter **B**.

The kit is equipped with the quick assembly kit of the manifold on the vacuum pump patented by Wigam.

All components are provided in comfortable trunk for simple handling.

Standard equipment:

- ATEX (Zone 2) vacuum pump RS3D-EX.
- 4 ways piston manifold, d. 80 oil filled pressure gauges, for R600a-R290-R1270.
- 2 flexible hoses 1500 mm, 1/4"SAE.
- 2 access valve LOCK-VALVE 1/4" - SAE F x 1/4" SAE M.
- 1 discharge vapour hose 5 m.
- Electronic scale 5kg, resolution 1g.
- 2 supports for cartridge (R290 and R600a).
- 1 mineral oil bottle.

Ref	Code	Model
A	01010008001	K-EX46D/D6
B	01010008003	K-EX-EV-46D/D6

Ref	Code	Dimensions	Weight
A	01010008001	550 x 330 x 360 mm	12,8 kg
B	01010008003	550 x 330 x 360 mm	12,8 kg



Technical features

Scale capacity	5 kg
Pump volume	46 l/min
Ultimate vacuum	1x10 ⁻² mbar



Spare parts



Ref	Code	Model	Description	Mn. Qty
A	06053010		Vapour exhaust pipe 5 m	-
B	06071002001	GYSS/4-4/60 B	Hose 1500 mm 1/4 x 1/4 - Blue	-
C	06071002002	GYSS/4-4/60 R	Hose 1500 mm 1/4 x 1/4 - Red	-
D	12002003	K1L	Mineral oil 1 l	12 pz