

## K-AZ200-50/BAZ50

### Kit azoto 5 litri

Utilizzabile per:

- Controllo perdite in pressione dei sistemi HVAC.
- Lavaggio sistemi HVAC.
- Flussaggio durante la saldatura in sistemi HVAC.
- Verifica taratura pressostati e manometri.

Kit composto da:

- Riduttore azoto serie AZ200-50 **con duplice connessione** integrata per cartucce e bombole.
- Manometro Ø80, classe 1.0 con settori definiti, indice di posizionamento e vite di regolazione.
- Tubo flessibile 1/4" SAE, 2500 mm + 220 mm
- Bombola azoto 5lt - TPED - piena (20 MPa).
- Adattatore RG180/5-4 (5/16" SAE F x 1/4" SAE M).

Codice	Modello	Paese	Attacchi bombole	Norma di riferimento	Attacchi cartucce
13005022001	K-AZ200-50/BAZ50	IT	W 21.7 x 1/14" M	UN 11144-5	M10x1



### Caratteristiche tecniche

Pressione ingresso riduttore	20 MPa
Pressione max. uscita	4,8 MPa
Attacchi	1/4" SAE
Dimensioni	700 x 430 x 280 mm
Peso	14,6 kg

## AZ200

### Riduttore professionale per bombole e cartucce

Riduttore professionale per eccellenza **con duplice connessione** integrata per cartucce e bombole (non richiede alcun adattatore esterno) e valvola di sicurezza "High Performance".

Codice	Modello	Paese	Attacchi bombole	Norma di riferimento	Attacchi cartucce
10002017	AZ200-50	IT	W 21.7 x 1/14" M	UN 11144-5	M10x1
10002019	AZ200-50/D	F-B-P-E	Ø21.7 x 1.814F	NF E 29-650/C	M10x1
10002018	AZ200-50/E	GB	G 5/8" M	BS 341 nr.3	-
10002020	AZ200-50/C	D	W 24.32 x 1/14" F	DIN 477 nr.10	M10x1



### Caratteristiche tecniche

Pressione ingresso	20 MPa
Pressione max. uscita	4,8 MPa
Attacchi	1/4" SAE
Dimensioni	380 x 200 x 130 mm
Peso	1,8 kg



## K-AZ200-50/BAZ50

### Nitrogen kit 5 liters

Suitable for:

- Testing for leaks in pressure of HVAC systems.
- Flushing of HVAC systems.
- Fluxing during soldering in HVAC systems.
- Pressure switches and gauges calibration.

Kit includes:

- Nitrogen regulator serie AZ200-50 with dual integrated connection for cartridges and bottles.
- Ø80 gauge, class 1.0 with defined sectors, positioning indicator and calibration screw.
- Flexible hose 1/4" SAE , 2500 mm + 220 mm.
- Nitrogen bottle 5 l - TPED - full (20 MPa).
- Adapter Rg180/5-4 (5/16" SAE Fx 1/4" SAE M).

Code	Model	Country	Cylinder connection	Standard reference	Cartridge connection
13005022001	K-AZ200-50/BAZ50	IT	W 21.7 x 1/14" M	UN 11144-5	M10x1



### Technical features

Regulator inlet pressure	20 MPa
Max output pressure	4,8 MPa
Connections	1/4" SAE
Dimensions	700 x 430 x 280 mm
Weight	14,6 kg

## AZ200

### "Heavy duty" nitrogen regulator for cartridges and cylinders

Heavy duty professional nitrogen regulator with dual integrated connection for cartridges and cylinders (no external adapter required) and "High Performance" safety valve.

Code	Model	Country	Cylinder connection	Standard reference	Cartridge connection
10002017	AZ200-50	IT	W 21.7 x 1/14" M	UN 11144-5	M10x1
10002019	AZ200-50/D	F-B-P-E	Ø21.7 x 1.814F	NF E 29-650/C	M10x1
10002018	AZ200-50/E	GB	G 5/8" M	BS 341 nr.3	-
10002020	AZ200-50/C	D	W 24.32 x 1/14" F	DIN 477 nr.10	M10x1



### Technical features

Inlet pressure	20 MPa
Max output pressure	4,8 MPa
Connections	1/4" SAE
Dimensions	380 x 200 x 130 mm
Weight	1,8kg

