

DISPOSITIVO OTTIMIZZAZIONE CARICA E CONTROLLO DELLE PRESSIONI DI ESERCIZIO

Il dispositivo, grazie ai suoi ridotti volumi interni ed alla facilità di regolazione, permette di ottimizzare il processo di carica degli impianti HVAC, massimizzando la precisione e riducendo al minimo la quantità di gas disperso.

Codice	Modello	Dimensioni	Peso
04001082	W1VRML80/D6/4/K1	220 x 240 x 70 mm	0,7 kg



BOMBOLE, RUBINETTI E SUPPORTI PER R600a

Bombole vuote a perdere con refrigerante R600a

Rif	Codice	Modello	Refrigerante	Qtà Refrig.	Attacchi	Qtà Min.	Peso
A	11001026	BF420/R600	R600a	420 gr	7/16"	12	0,60 kg

Rubinetti e supporti per bombole vuote a perdere R600a

Rif	Codice	Modello	Descrizione	Attacchi
B	05002003001	BVR-4	Rubinetto	7/16" F x 1/4" SAE M
C	05104038		Supporto + tubo 90°	7/16" F x 1/4" SAE F



BOMBOLE, RUBINETTI E SUPPORTI PER R290

Bombole vuote a perdere con refrigerante R290

Rif	Codice	Modello	Refrig.	Qtà Refrig.	Attacchi	Qtà Min.	Peso
A	11001085	BF370/R290	R290	370 gr	1/2" 16 ACMESX	12	1,15 kg

Rubinetti e supporti per bombole vuote a perdere R290

Rif	Codice	Modello	Descrizione	Attacchi
B	05002035001	121 RGAS-4-WIG	Rubinetto	1/2" - 16 ACME SX F x 1/4" SAE M
C	05104052		Supporto + tubo 90°	1/2" - 16 ACME SX F x 1/4" SAE F
D	050590076	LOCK-VALVE/AS-4	Valvola di accesso	1/2"-16 ACME SX F x 1/4" SAE M



CHARGING OPTIMIZATION DEVICE AND CONTROL OF WORKING PRESSURES

Thanks to its small inner volumes and to its easy regulation, the device allows to optimize the HVAC systems charging process, maximizing the accuracy and reducing at the lowest the quantity of dissipated refrigerant.

Code	Model	Dimensions	Weight
04001082	W1VRML80/D6/4/K1	220 x 240 x 70 mm	0,7 kg



CARTRIDGES, VALVES AND SUPPORTS FOR R600A

Disposable cartridges with refrigerant R600a

Ref	Code	Model	Refrigerant	Refrig. Qty	Connections	Mn. Qty	Weight
A	11001026	BF420/R600	R600a	420 gr	7/16"	12	0,60 kg

Valves and supports for disposable cartridges R600a

Ref	Code	Model	Description	Connections
B	05002003001	BVR-4	Valve	7/16" F x 1/4" SAE M
C	05104038		Support + 90° hose	7/16" F x 1/4" SAE F



CARTRIDGES, VALVES AND SUPPORTS FOR R290

Disposable cartridges with refrigerant R290

Ref	Code	Model	Refrig.	Refrig. Qty	Connections	Mn. Qty	Weight
A	11001085	BF370/R290	R290	370 gr	1/2" 16 ACME SX	12	1,15 kg

Valves and supports for disposable cartridges R290

Ref	Code	Model	Description	Connections
B	05002035001	121 RGAS-4-WIG	Valve	1/2" - 16 ACME SX F x 1/4" SAE M
C	05104052		Support + 90° hose	1/2" - 16 ACME SX F x 1/4" SAE F
D	05059076	LOCK-VALVE/AS-4	Access valve	1/2"-16 ACME SX F x 1/4" SAE M

