

## DISPOSITIVO OTTIMIZZAZIONE CARICA E CONTROLLO DELLE PRESSIONI DI ESERCIZIO

Il dispositivo, grazie ai suoi ridotti volumi interni ed alla facilità di regolazione, permette di ottimizzare il processo di carica degli impianti HVAC, massimizzando la precisione e riducendo al minimo la quantità di gas disperso.

| Codice   | Modello          | Dimensioni        | Peso   |
|----------|------------------|-------------------|--------|
| 04001082 | W1VRML80/D6/4/K1 | 220 x 240 x 70 mm | 0,7 kg |



## BOMBOLE, RUBINETTI E SUPPORTI PER R600a

Bombole vuote a perdere con refrigerante R600a

| Rif      | Codice   | Modello    | Refrigerante | Q.tà Refrig. | Attacchi | Q.tà Min. | Peso    |
|----------|----------|------------|--------------|--------------|----------|-----------|---------|
| <b>A</b> | 11001026 | BF420/R600 | R600a        | 420 gr       | 7/16"    | 12        | 0,60 kg |

Rubinetti e supporti per bombole vuote a perdere R600a

| Rif      | Codice      | Modello | Descrizione         | Attacchi             |
|----------|-------------|---------|---------------------|----------------------|
| <b>B</b> | 05002003001 | BVR-4   | Rubinetto           | 7/16" F x 1/4" SAE M |
| <b>C</b> | 05104038    |         | Supporto + tubo 90° | 7/16" F x 1/4" SAE F |



## BOMBOLE, RUBINETTI E SUPPORTI PER R290

Bombole vuote a perdere con refrigerante R290

| Rif      | Codice   | Modello    | Refrig. | Q.tà Refrig. | Attacchi       | Q.tà Min. | Peso    |
|----------|----------|------------|---------|--------------|----------------|-----------|---------|
| <b>A</b> | 11001085 | BF370/R290 | R290    | 370 gr       | 1/2" 16 ACMESX | 12        | 1,15 kg |

Rubinetti e supporti per bombole vuote a perdere R290

| Rif      | Codice      | Modello         | Descrizione         | Attacchi                         |
|----------|-------------|-----------------|---------------------|----------------------------------|
| <b>B</b> | 05002035001 | 121 RGAS-4-WIG  | Rubinetto           | 1/2" - 16 ACME SX F x 1/4" SAE M |
| <b>C</b> | 05104052    |                 | Supporto + tubo 90° | 1/2" - 16 ACME SX F x 1/4" SAE F |
| <b>D</b> | 050590076   | LOCK-VALVE/AS-4 | Valvola di accesso  | 1/2" - 16 ACME SX F x 1/4" SAE M |



## CHARGING OPTIMIZATION DEVICE AND CONTROL OF WORKING PRESSURES

Thanks to its small inner volumes and to its easy regulation, the device allows to optimize the HVAC systems charging process, maximizing the accuracy and reducing at the lowest the quantity of dissipated refrigerant.

| Code     | Model            | Dimensions        | Weight |
|----------|------------------|-------------------|--------|
| 04001082 | W1VRML80/D6/4/K1 | 220 x 240 x 70 mm | 0,7 kg |



## CARTRIDGES, VALVES AND SUPPORTS FOR R600A

Disposable cartridges with refrigerant R600a

| Ref      | Code     | Model      | Refrigerant | Refrig. Qty | Connections | Mn. Qty | Weight  |
|----------|----------|------------|-------------|-------------|-------------|---------|---------|
| <b>A</b> | 11001026 | BF420/R600 | R600a       | 420 gr      | 7/16"       | 12      | 0,60 kg |

Valves and supports for disposable cartridges R600a

| Ref      | Code        | Model | Description        | Connections          |
|----------|-------------|-------|--------------------|----------------------|
| <b>B</b> | 05002003001 | BVR-4 | Valve              | 7/16" F x 1/4" SAE M |
| <b>C</b> | 05104038    |       | Support + 90° hose | 7/16" F x 1/4" SAE F |



## CARTRIDGES, VALVES AND SUPPORTS FOR R290

Disposable cartridges with refrigerant R290

| Ref      | Code     | Model      | Refrig. | Refrig. Qty | Connections     | Mn. Qty | Weight  |
|----------|----------|------------|---------|-------------|-----------------|---------|---------|
| <b>A</b> | 11001085 | BF370/R290 | R290    | 370 gr      | 1/2" 16 ACME SX | 12      | 1,15 kg |

Valves and supports for disposable cartridges R290

| Ref      | Code        | Model           | Description        | Connections                      |
|----------|-------------|-----------------|--------------------|----------------------------------|
| <b>B</b> | 05002035001 | 121 RGAS-4-WIG  | Valve              | 1/2" - 16 ACME SX F x 1/4" SAE M |
| <b>C</b> | 05104052    |                 | Support + 90° hose | 1/2" - 16 ACME SX F x 1/4" SAE F |
| <b>D</b> | 05059076    | LOCK-VALVE/AS-4 | Access valve       | 1/2"-16 ACME SX F x 1/4" SAE M   |

