

X-TFC

Sonda di temperatura a morsetto

- Dispositivo completamente indipendente grazie al display OLED da 1" e al controllo a bordo.
- Sensore a termocoppia per una maggiore accuratezza (+/- 0,5°C).
- Memoria integrata.
- Batteria al litio ricaricabile (USB-C).
- Connessione Bluetooth 5.0 per l'App MyWIGAM e gli Smart Tools WIGAM.
- Compatibile con tutti i gruppi digitali della gamma X-MAN.
- App MyWIGAM (iOS e Android) con dati e report in tempo reale.
- Le informazioni provenienti da diversi dispositivi, come sonde di temperatura e manometri aggiuntivi, sono combinate nell'App MyWIGAM per fornire uno scenario completo.



Rif	Codice	Modello	Descrizione
A	09011061	X-TFC	Sonda a morsetto Bluetooth
B	09011063	K-X-TFC	Kit 2 sonde a morsetto in custodia

CARATTERISTICHE TECNICHE

Intervallo di temperatura	-40 ÷ 150°C	Unità di misura	°C, °F; K
Risoluzione	0,1°C	Raggio azione Bluetooth	100m
Precisione	+/- 0,5°C	Alimentazione	Batteria litio ricaricabile (USB-C)



Taratura

Codice	Descrizione
09053057	Rapporto di taratura X-TFC
09011061001	X-TFC/RT sonda completa di rapporto di taratura




Fino a 40 mm




Tecnologia Bluetooth



Stand-alone



Memoria integrata fino a 3000 registrazioni



Batteria litio ricaricabile (USB-C)

X-TFC

Clamp temperature probe

- Fully independent device thanks to its 1" OLED display and onboard control.
- Thermocouple sensor for higher accuracy ($\pm 0.5^{\circ}\text{C}$).
- Built-in memory.
- Rechargeable lithium battery (USB-C).
- Bluetooth 5.0 connection for MyWIGAM App and WIGAM Smart Tools.
- Compatible with all digital manifolds of the X-MAN range.
- MyWIGAM App (iOS and Android) with real-time data and reports.
- Data from multiple devices, such as temperature probes and additional gauges, are combined within the MyWIGAM App to provide a complete overview.



Ref	Code	Model	Description
A	09011061	X-TFC	Bluetooth clamp probe
B	09011063	K-X-TFC	Kit of 2 probes in protective bag



TECHNICAL FEATURES

Temperature range	$-40 \div 150^{\circ}\text{C}$	Unit of measure	$^{\circ}\text{C}$, $^{\circ}\text{F}$, K
Resolution	0.1°C	Bluetooth operating range	100m
Accuracy	$\pm 0.5^{\circ}\text{C}$	Power supply	Rechargeable lithium battery (USB-C)



Calibration

Code	Description
09053057	Calibration report for X-TFC
09011061001	X-TFC/RT probe with calibration report




Up to 40 mm




Bluetooth technology



Stand-alone



Built-in memory for up to 3000 recordings



Rechargeable lithium battery (USB-C)