

UNITÀ DI RECUPERO

NUOVO

INCLUSO
R32

INCLUSO
R1234ze

CONFORMITÀ
ISO 11650
IEC60335-2-104

NF EN38421
CE N.1005 2009
UE-517/2014



NUOVO DISPLAY DIGITALE

Velocità di recupero	R1234ze- R134a	R502- R407C	R404A-R410A- R507-R32
Vapore	29 kg/h	32 kg/h	33 kg/h
Liquido (recupero)	214 kg/h	340 kg/h	380 kg/h
Push-pull	372 kg/h	474 kg/h	502 kg/h

EASYREC-3

Unità di recupero ad alte prestazioni per CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze)

- Alte performance grazie al potente compressore da 1HP e al condensatore di superiore capacità.
- Design super compatto e leggero.
- Cilindri ceramici con tenuta in fibra di carbonio per superiore affidabilità.
- Ampio e intuitivo display digitale Heavy Duty che supporta il frigorista nelle fasi di recupero con molteplici informazioni.
- Molteplici modalità di recupero semplicemente selezionabili.
- Arresto automatico al termine del recupero con indicazione visiva e acustica.
- Valvole di intercettazione che evitano la fuoriuscita di refrigerante.
- Dispositivo di auto evacuazione (PURGE) che permette di cambiare facilmente il tipo di refrigerante
- Dispositivo di sicurezza pressione massima.
- Spia e filtro inclusi.

Codice	Modello	Dimensioni con imballo	Peso con imballo
13001028	EASYREC-3	380 x 360 x 250 mm	10,90 kg



Caratteristiche tecniche:

Refrigeranti	CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze)
Alimentazione	220 - 240V AC 50 - 60 Hz
Potenza motore	750W
Max corrente assorbita	6A
Compressore	Doppio pistone, a secco
Blocco automatico di sicurezza	38.5 bar/3850 kPa (558 psi)
Temperatura di esercizio	0 - 40 °C



Ricambi e accessori



Rif	Codice	Modello	Descrizione	Dimensioni	Peso
A	14015008	MG-111	Filtro disidratatore (1/4" SAE M-M)	100 x 40 x 40 mm	0,28 kg
A	14015041	MG-111-A	Filtro disidratatore con allumina (1/4"SAE M-M)	100 x 40 x 40 mm	0,28 kg
B	14015013	XH412	Filtro disidratatore "alta capacità" (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
B	14015042	XH412-A	Filtro disidratatore con allumina "alta capacità" (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
C	14020014001	G19020-WIG	Kit di 10 guarnizioni per tubi flessibili 1/4" SAE	160 x 90 x 10 mm	0,02 kg
D	06071013003	GYSS/4-4/6/Y	Tubo collegamento filtro 1/4" SAE 150 mm	250 x 50 x 50 mm	0,16 kg
E	13008026	REC026	Spia liquido/umidità	90 x 40 x 50 mm	0,17 kg

RECOVERY UNIT

NEW



NEW DIGITAL DISPLAY

Recovery rate	R1234ze-R134a	R502-R407C	R404A-R410A-R507-R32
Vapour	29 kg/h	32 kg/h	33 kg/h
Liquid (recovery)	214 kg/h	340 kg/h	380 kg/h
Push-pull	372 kg/h	474 kg/h	502 kg/h

EASYREC-3

High performance recovery unit for CFC, HCFC, HFC and HFO (included R32 and R1234ze)

- High performances thanks to the powerful 1 HP compressor and to the higher capacity condenser.
- Very compact and light design.
- Ceramic cylinders with carbon fibre seal for superior reliability.
- Large, intuitive heavy-duty digital display that supports the user in the recovery phase with multiple information.
- Multiple selectable recovery modes.
- Automatic stop of the unit at the end of recovery with visual and acoustic indication.
- Shut-off valves that prevent refrigerant spills.
- Self-evacuation (PURGE) device, which allows to change type of refrigerant easily.
- Safety device for maximum pressure.
- Sight-glass and filters included.

Code	Model	Dimensions with pack	Weight with pack
13001028	EASYREC-3	380 x 360 x 250 mm	10,90 kg



Technical features

Refrigerant	CFC, HCFC, HFC e HFO (included R32 e R1234ze)
Power supply	220 - 240V AC 50 - 60 Hz
Motor power	750W
Maximal current draw	6A
Compressor	Double piston, dry
Automatic safety shut-off	38.5 bar/3850 kPa (558 psi)
Operating temperature	0 - 40 °C



Spare parts and accessories



Ref	Code	Model	Description	Dimensions	Weight
A	14015008	MG-111	Filter drier (1/4" SAE M-M)	100 x 40 x 40 mm	0,28 kg
A	14015041	MG-111-A	Filter drier (1/4" SAE M-M) with alumina	100 x 40 x 40 mm	0,28 kg
B	14015013	XH412	"High capacity" filter drier (1/4" SAE M-M)	250 x 80 x 80 mm	1,10 kg
B	14015042	XH412-A	"High capacity" filter drier (1/4" SAE M-M) with alumina	250 x 80 x 80 mm	1,10 kg
C	14020014001	G19020-WIG	Kit 10 gaskets for 1/4" SAE flexible hoses	160 x 90 x 10 mm	0,02 kg
D	06071013003	GYSS/4-4/6/Y	Connection hose for filter 1/4" SAE 150 mm	250 x 50 x 50 mm	0,16 kg
E	13008026	REC026	Sight glass	90 x 40 x 50 mm	0,17 kg