

CLAMP-ONE

Pinza amperometrica digitale wireless

- Valore massimo di 3999.
- Puntali di alta qualità.
- Misurazione Corrente AC fino a 1000A.
- Circuito ohmico, diodo, continuità, capacità, frequenza protettivo fino a 750V AC/DC rms.
- Test diodo con cicalino di verifica della continuità.
- Auto-spegnimento per preservare la durata della batteria.
- Display retroilluminato.
- Provvisto di DATA-HOLD, RELATIVE.
- Dotata di sonda di temperatura esterna.



**INDISPENSABILE
PER CONTROLLARE
L'APPARECCHIATURA INVERTER**


Specifiche elettriche

| | Range |
|-------------|---|
| Tensione DC | 400mV, 4V, 40V, 400V, 1000V |
| Tensione AC | 4V, 40V, 400V, 750V |
| Corrente DC | 200A, 1000A |
| Corrente AC | 400A, 1000A |
| Resistenza | 400Ω, 40KΩ, 400KΩ, 4MΩ, 40MΩ |
| Capacità | 5124F, 5, 124F, 51.24F, 100 4F |
| Temperatura | -20 ÷ 1000 °C |
| Frequenza | 5.12Hz, 51.2Hz, 512Hz, 5.12kHz, 512kHz, 5.12MHz |
| Ciclo Duty | 0.1% ÷ 99.9% |


Taratura

| Codice | Modello | Descrizione |
|-------------|--------------|---|
| 09053017 | | Rapporto taratura rif. Accredia per pinza |
| 09006008001 | CLAMP-ONE/CT | Pinza completa di rapporto taratura |

**INTERCONNESSIONE
CON FOX-ONE**



**PHONE
APP**



CLAMP-ONE

Wireless digital clamp-on meter

- Maximum reading of 3999.
- Heavy duty test leads.
- ACA Measurement up to 1000A.
- Ohm, Diode, Continuity, Capacitance, Frequency and Duty input Protection to 750V DA/AC rms.
- Diode test and Audible continuity check function.
- Auto power off to preserve battery life.
- Display back-light feature.
- Provides DATA-HOLD, RELATIVE.
- Complete of external temperature probe.

| Code | Model | Dimensions | Weight |
|----------|-----------|------------------|---------|
| 09006008 | CLAMP-ONE | 225 x 97 x 40 mm | 0,45 kg |



Electrical specifications

| | Range |
|--------------|---|
| DC voltage | 400mV, 4V, 40V, 400V, 1000V |
| AC voltage | 4V, 40V, 400V, 750V |
| DC current | 200A, 1000A |
| AC current | 400A, 1000A |
| Resistance | 400Ω, 40KΩ, 400KΩ, 4MΩ, 40mΩ |
| Quantity | 5124F, 5, 124F, 51.24F, 100 4F |
| Temperature | -20 to 1000 °C |
| Frequency | 5.12Hz, 51.2Hz, 512Hz, 5.12kHz, 512kHz, 5.12MHz |
| Duty current | 0.1% to 99.9% |



Calibration

| Code | Model | Description |
|-------------|--------------|---|
| 09053017 | | Calibration report ref. Accredia for clamp-on meter |
| 09006008001 | CLAMP-ONE/CT | Clamp-on meter with calibration report |

INDISPENSABLE FOR INVERTER UNITS CHECK



COMPATIBLE APPS WITH FOX-ONE



PHONE APP

