

RELAYS



ICG

Relays per sistemi frigoriferi senza condensatori di spunto.

Codice	Modello	Dimensioni	Peso
09016002	ICG-220	140 x 120 x 20 mm	0,05 kg



RO

Relays con combinazione di sovraccarico.

Codice	Modello	Dimensioni	Peso
09016001	RO-82	140 x 120 x 40 mm	0,07 kg
09016004	RO-62	140 x 120 x 40 mm	0,07 kg
09016003	RO-42	140 x 120 x 40 mm	0,07 kg



PO

Relays per sistemi frigoriferi senza condensatori di spunto.

Codice	Modello	Dimensioni	Peso
09016017	PO-230	120 x 100 x 20 mm	0,03 kg



RCO

Relays di avviamento 3 in 1.

Codice	Modello	Dimensioni	Peso
09016033	RCO-820	190 x 180 x 40 mm	0,20 kg
09016009	RCO-620	190 x 180 x 40 mm	0,20 kg
09016011	RCO-420	190 x 180 x 40 mm	0,20 kg



Tabella comparativa

	ICG-220	PO-230	RO-82	RO-62	RO-42	RCO-820	RCO-620	RCO-420
Relay	X	X	X	X	X	X	X	X
Sovraccarico	-	-	X	X	X	X	X	X
Condensatore avviamento	-	-	-	-	-	X	X	X
Montaggio	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect
Potenza HP	1/12÷1/2	1/12÷1/2	1/12÷1/8	1/6÷1/5	1/4÷1/3	1/12÷1/8	1/6÷1/5	1/4÷1/3
Vtaggio	230	230	230	230	230	230	230	230

RELAYS



ICG

Relays and hard starts for refrigeration systems without run capacitors.

Code	Model	Dimensions	Weight
09016002	ICG-220	140 x 120 x 20 mm	0,05 kg



RO

Relays and hard starts for refrigeration systems without run capacitors.

Code	Model	Dimensions	Weight
09016001	RO-82	140 x 120 x 40 mm	0,07 kg
09016004	RO-62	140 x 120 x 40 mm	0,07 kg
09016003	RO-42	140 x 120 x 40 mm	0,07 kg



PO

Relays with overload combination.

Code	Model	Dimensions	Weight
09016017	PO-230	120 x 100 x 20 mm	0,03 kg



RCO

3 n° 1 Start Relay.

Code	Model	Dimensions	Weight
09016033	RCO-820	190 x 180 x 40 mm	0,20 kg
09016009	RCO-620	190 x 180 x 40 mm	0,20 kg
09016011	RCO-420	190 x 180 x 40 mm	0,20 kg



Comparative table

	ICG-220	PO-230	RO-82	RO-62	RO-42	RCO-820	RCO-620	RCO-420
Relay	x	x	x	x	x	x	x	x
Overload	-	-	x	x	x	x	x	x
Start capacitor	-	-	-	-	-	x	x	x
Mounting	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect	Quick connect
HP rating	1/12 to 1/2	1/12 to 1/2	1/1 2to 1/8	1/6 to 1/5	1/4 to 1/3	1/12 to 1/8	1/6 to 1/5	1/4 to 1/3
Voltage	230	230	230	230	230	230	230	230