



ELEVATA CAPACITÀ  
DI RECUPERO E RICICLO



## EASYREC-HP

Ideale per recuperi e ricicli di grandi quantitativi di refrigerante

- Utilizzabile con CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze).
- Sistema di distillazione integrato con controllo automatico flusso del refrigerante che permette la separazione di olio/impurità/additivi ad alta efficacia.
- Dispositivo di auto evacuazione (PURGE) che permette facilmente il passaggio da un refrigerante ad un altro.
- Dispositivo di arresto automatico al termine del ciclo di recupero-riciclo (spia verde accesa).
- Pressostato di sicurezza (spia rossa - allarme).
- Valvole di intercettazione che evitano la fuoriuscita di refrigerante.
- Manometri pulse free Ø80 con vite di regolazione.
- Tubi flessibili 1500 mm con valvole di intercettazione.
- Due filtri in aspirazione e uno in mandata.
- Due indicatori di passaggio in aspirazione.
- Ampia grafica con istruzioni rapide di funzionamento.

Codice	Modello	Dimensioni	Peso
13001025	EASYREC-HP	605 x 570 x 800 mm	65 kg



### Caratteristiche tecniche:

Refrigeranti	CFC, HCFC, HFC e HFO (inclusi R32 e R1234ze)
Alimentazione	230/1/50
Potenza motore	1800W
Max corrente assorbita	8A
Compressore	Lubrificato
Blocco automatico di sicurezza	37 bar
Temperatura di esercizio	10 - 50 °C

### Velocità di recupero

Recupero-riciclo	60 kg/h
Push-pull	660 kg/h



### Ricambi e accessori

Codice	Modello	Descrizione	Qtà Min.
14015008	MG-111	Filtro disidratatore (1/4" SAE M-M)	-
14015041	MG-111-A	Filtro disidratatore con allumina (1/4"SAE M-M)	-
14015013	XH412	Filtro disidratatore "alta capacità" (1/4" SAE M-M)	-
14015042	XH412-A	Filtro disidratatore con allumina "alta capacità" (1/4" SAE M-M)	-
13008026	REC026	Spia liquido/umidità	-
06077002001	V/GYSS/4-4/60B	Tubo fless. blu 1500 mm c/valvola	-
06077002002	V/GYSS/4-4/60R	Tubo fless. rosso 1500 mm c/valvola	-
06077002003	V/GYSS/4-4/60Y	Tubo fless. giallo 1500 mm c/valvola	-
06071013003	GYSS/4-4/6/Y	Tubo collegamento filtro 1/4" SAE 150 mm	-
12002017	W68	Olio estere 1000 cc	9 pz

# "HIGH PERFORMANCE" RECOVERY - RECYCLING UNIT



HIGH PERFORMANCE



## EASYREC-HP

The ideal recovery-recycling unit for large refrigeration systems with high quantities of refrigerant

- Suitable for CFC-HCFC, HFC and HFO (included R32 and R1234ze).
- Distillation device with automatic refrigerant flow check, which allows to separate oil/impurity/dyes very efficiently.
- Self evacuation system (PURGE) which allows to change the type of refrigerant easily.
- Automatic stop system at the end of the recovery-recycling cycle (green light on).
- Safety pressure switch (red light on – alarm).
- Cut-off valves to prevent refrigerant discharge.
- Ø80 pulse free gauges with adjustment screw.
- Flexible hoses 1500mm with valves.
- Two filters in suction side and one filter in pressure side.
- Sight glasses in suction side.
- Large panel with quick functioning instructions.

Code	Model	Dimensions	Weight
13001025	EASYREC-HP	605 x 570 x 800 mm	65 kg



## Technical features

Refrigerant	CFC, HCFC, HFC and HFO (included R32 and R1234ze)
Power supply	230/1/50
Motor power	1800W
Maximal current draw	8A
Compressor	With oil
Automatic safety shut-off	37 bar
Operating temperature	10 ÷ 50 °C

## Recovery rate

Recovery-recycling	60 kg/h
Push-pull	660 kg/h



## Spare parts and accessories

Code	Model	Description	Min. Qty
14015008	MG-111	Filter drier (1/4" SAE M-M)	-
14015041	MG-111-A	Filter drier (1/4" SAE M-M) with alumina	-
14015013	XH412	"High capacity" drier filter (1/4" SAE M-M)	-
14015042	XH412-A	"High capacity" drier filter (1/4" SAE M-M) with alumina	-
13008026	REC026	Sight glass	-
06077002001	V/GYSS/4-4/60B	Blue flexible hose 1500 mm with valve	-
06077002002	V/GYSS/4-4/60R	Red flexible hose 1500 mm with valve	-
06077002003	V/GYSS/4-4/60Y	Yellow flexible hose 1500 mm with valve	-
06071013003	GYSS/4-4/6/Y	Filter connection tube 1/4" SAE 150 mm	-
12002017	W68	Ester oil 1000 cc	9 pz



WIGAM S.p.A.  
Loc.Spedale 10/b  
52018 Castel San Niccolò  
(AR) Italy  
Tel. 0575 / 5011  
Fax. 0575 / 501200

---

## Dichiarazione di Conformità



---

Noi, firmatari della presente, dichiariamo sotto la nostra esclusiva responsabilità, che la macchina, modello :

**EASYREC HP**  
e tutte le proprie varianti

costruite nella nostra azienda e destinate ad essere utilizzate per :

recuperare gas refrigerante

sono progettate secondo quanto prescritto dalle direttive :

- **2014/30/UE (Direttiva sulla compatibilità elettromagnetica)**
- **2014/35/UE (Direttiva sulla bassa tensione)**
- **IEC 34-11 (EN 60034) Requisiti generali per macchine elettriche rotanti monofase**

Le prestazioni del recuperatore soddisfano i requisiti della norma EN 35 421

Castel San Niccolò  
10/02/2017

Gastone Vangelisti  
(Presidente)

A handwritten signature in black ink, appearing to read 'Gastone Vangelisti', written over a white background.



Loc.Spedale 10/b  
52018 Castel San Niccolò  
(AR) Italy  
Tel. 0575 / 5011  
Fax. 0575 / 501200

---

# CE Declaration of Conformity

---

We, signers of this declaration, declare under our own exclusive responsibility, that unit, model:

**EASYREC HP**  
And all its variants

manufactured in our company and to be used for:

recover refrigerant gas

**Are designed according to the following directives prescriptions:**

- **2014/30/UE Directive on electromagnetic compatibility**
- **2014/35/UE Directive on low voltage**
- **IEC 34-11 (EN 60034) General standards on single phase electric, rotative machines**

The performance of this recovery unit complies with the norm EN 35 421.

10/02/2017

Gastone Vangelisti  
(President)

A handwritten signature in black ink, appearing to read 'Gastone Vangelisti'.