

## SIGILLANTI



### 10001

Frena-filetti

| Codice   | Modello | Capacità | Dimensioni         | Peso   | Q.tà Min. |
|----------|---------|----------|--------------------|--------|-----------|
| 12003002 | 10001   | 40 cc    | 145 x 100 x 100 mm | 0,6 kg | 12        |



### HST

Sigillante epossidico

Ferma le fughe facilmente.

Permette di effettuare riparazioni epossidiche solide e curate in meno di 90 secondi.

Si scioglie e si indurisce in una sola operazione.

Permette la rimessa in funzione immediata.

Efficace per qualsiasi sistema refrigerante.

Resiste ad una pressione di 41 bar.

Resiste ad una temperatura di 177°C.

Efficace su tutti i metalli, la ceramica e anche sul vetro.

Per tutti i sistemi refrigeranti.

| Codice   | Modello | Capacità | Dimensioni         | Peso    | Q.tà Min. |
|----------|---------|----------|--------------------|---------|-----------|
| 12003004 | HST     | 11,7 g   | 140 x 120 x 150 mm | 0,35 kg | 12        |



### L542/LX53-14

Sigillanti per raccordi filettati

| Rif | Codice   | Modello | Capacità | Dimensioni        | Peso   | Q.tà Min. |
|-----|----------|---------|----------|-------------------|--------|-----------|
| A   | 12003005 | L542    | 50 cc    | 180 x 110 x 60 mm | 1 kg   | 12        |
| B   | 12003008 | LX53-14 | 50 cc    | 150 x 55 x 30 mm  | 0,8 kg | 10        |



### NAC10

Nastro anticondensa flessibile retinato per isolamento termico

Nastro anticondensa in gomma sintetica.

Dimensioni rotolo: 0,03 x 50 mm x 10 m.

| Codice   | Modello | Temp. utilizzo | Dimensioni Conf.   | Peso Conf. | Q.tà Min. |
|----------|---------|----------------|--------------------|------------|-----------|
| 12004001 | NAC10   | -25°C +120°C   | 450 x 450 x 320 mm | 4,5kg      | 24        |



### NAL50

Nastro alluminio adesivo

Nastro alluminio adesivo supporto carta siliconata.

Dimensioni rotoli: 0,03 x 50 mm x 50 m.

| Codice   | Modello | Dimensioni Conf.   | Peso Conf. | Q.tà Min. |
|----------|---------|--------------------|------------|-----------|
| 12004002 | NAL50   | 270 x 270 x 320 mm | 11 kg      | 24        |

## SEALERS

**10001**

Thread locker

| Code     | Model | Capacity | Dimensions         | Weight | Min. Qty |
|----------|-------|----------|--------------------|--------|----------|
| 12003002 | 10001 | 40 cc    | 145 x 100 x 100 mm | 0,6 kg | 12       |

**HST**

Epoxy Sealer

Stops leaks fast.

Makes tough, cured, epoxy repairs in as little as 90 seconds.

Melts and cures in one operation.

Restores service immediately.

Effective for all refrigeration systems.

Withstands pressure to 600 psi.

Resists temperatures to 350°F (177°C).

Works on all metals, ceramics, even glass.

Seals all refrigeration systems.

| Code     | Model | Capacity | Dimensions         | Weight  | Min. Qty |
|----------|-------|----------|--------------------|---------|----------|
| 12003004 | HST   | 11,7 g   | 140 x 120 x 150 mm | 0,35 kg | 12       |

**A****B****L542/LX53-14**

Threaded sealers

| Rif      | Code     | Model   | Capacity | Dimensions        | Weight | Min. Qty |
|----------|----------|---------|----------|-------------------|--------|----------|
| <b>A</b> | 12003005 | L542    | 50 cc    | 180 x 110 x 60 mm | 1 kg   | 12       |
| <b>B</b> | 12003008 | LX53-14 | 50 cc    | 150 x 55 x 30 mm  | 0,8 kg | 10       |

**NAC10**

Anti-condensation flexible and reinforced ribbon for heat insulation

Anti-condensation ribbon in synthetic rubber.

Rolls dimensions: 0,03 x 50 mm x 10 m.

| Code     | Model | Operating temp. | Dimensions Pack    | Weight Pack | Min. Qty |
|----------|-------|-----------------|--------------------|-------------|----------|
| 12004001 | NAC10 | -25°C +120°C    | 450 x 450 x 320 mm | 4,5kg       | 24       |

**NAL50**

Alluminium adhesive ribbon

Alluminium adhesive ribbon with silicon paper support.

Rolls dimensions: 0,03 x 50 mm x 50 m

| Code     | Model | Dimensions         | Weight | Min. Qty |
|----------|-------|--------------------|--------|----------|
| 12004002 | NAL50 | 270 x 270 x 320 mm | 11 kg  | 24       |