

KIT UUOTO E CARICA K-PGTB



SCALE REFRIGERANTI

A3 R600a

A4 R410A-R32

A6 R22-R134a-R404A-R407C

D6 R600a-R290-R1270

K-PGTB

Sistema vuoto e carica con bilancia elettronica da 5 kg

Il sistema di accoppiamento rapido pompa vuoto - elettrovalvola -vacuometro- gruppo manometrico, brevettato dalla Wigam, permette di sostituire molto velocemente di volta in volta il gruppo manometrico a seconda del refrigerante con il quale andremo ad operare e di avere una stazione vuoto-carica estremamente compatta e facile da trasportare.

Dotazione in funzione della scala refrigerante selezionata:

- Pompa doppio stadio 46 lt/min con raccordo rigido in aspirazione femmina girevole da 3/8"SAE.
- Gruppo manometrico a 4 vie con manometri Ø80 classe 1.
- Bilancia elettronica fino a 5 kg, risoluzione 1 g.
- Supporto e tubo capillare per bombole.
- 2 tubi flessibili 1500 mm con valvola intermedia.
- 1 tubo di scarico vapore 5 m (solo versioni A3 e D6).
- Bauletto in plastica.

Codice	Modello
01010001	K-PGTB-A4
01010002	K-PGTB-A6
01010013	K-PGTB-A3
01010014	K-PGTB-D6

Codice	Dimensioni	Peso
01010001	520 x 290 x 340 mm	19 kg
01010002	520 x 290 x 340 mm	22 kg
01010013	520 x 290 x 340 mm	22 kg
01010014	520 x 290 x 340 mm	25 kg



Bombole non incluse nel kit



Caratteristiche tecniche

	K-PGTB-A4	K-PGTB-A6	K-PGTB-A3	K-PGTB-D6
Refrigeranti	R410A-R32	R22-R134a-R404C-R407C	R600a	R600a-R290-R1270
Portata bilancia	5 kg	5 kg	5 kg	5 kg
Portata pompa	46 lt/min	46 lt/min	46 lt/min	46 lt/min
Vuoto finale	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar
Attacchi	5/16" SAE	1/4" SAE	1/4" SAE	1/4" SAE
Supporti	2 pz.	1 pz.	1 pz.	2 pz.

VACUUM AND CHARGING KIT

Refrigerants dials

A3 R600a A4 R410A-R32 A6 R22-R134a-R404A-R407C D6 R600a-R290-R1270

K-PGTB

Vacuum and charging system with electronic scale 5kg

The quick coupling system, patented by Wigam, for vacuum pump - solenoid valve - vacuum gauge - manifold assembly, allows to replace the manifold very quickly each time you need to operate with a different refrigerant and to have a very compact and easy to carry vacuum and charging station.

Standard equipment:

- 46 l double stage vacuum pump with female rigid swivel connection 3/8" SAE .
- 4-way manifold with Ø80 gauges, class 1.
- electronic scale up to 5 kg, resolution 1 gr
- 2 flexible hoses 1500 mm with intermediate valve.
- 1 vapour discharge hose (only versions A3 and D6)
- plastic case

Code	Model
01010001	K-PGTB-A4
01010002	K-PGTB-A6
01010013	K-PGTB-A3
01010014	K-PGTB-D6

Code	Dimensions	Weight
01010001	520 x 290 x 340 mm	19 kg
01010002	520 x 290 x 340 mm	22 kg
01010013	520 x 290 x 340 mm	22 kg
01010014	520 x 290 x 340 mm	25 kg



Bottles not included in the kit



Technical features

	K-PGTB-A4	K-PGTB-A6	K-PGTB-A3	K-PGTB-D6
Refrigerants	R410A-R32	R22-R134a-R404C-R407C	R600a	R600a-R290-R1270
Scale capacity	5 kg	5 kg	5 kg	5 kg
Pump volume	46 lt/min	46 lt/min	46 lt/min	46 lt/min
Ultimate vacuum	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar	1x10 ⁻² mbar
Connections	5/16" SAE	1/4" SAE	1/4" SAE	1/4" SAE
Supports	2 pcs	1 pc	1 pc	2 pcs